



# Introduction

Name: ZL-5006A T Martin date Abrasimeter



**Description Of Goods:**

## Applicable Range

Used for testing the performance of the wearing resistance, abrasion, appearance change (pilling degree/class) of the textiles and membrane materials.

## Relevant Standards

Tel: [+86-769-3365 7986](tel:+86-769-33657986)

Fax: [+86-769-83365 7987](tel:+86-769-833657987)

Website: [www.zltester.com](http://www.zltester.com)

E-mail: [Zhongli@zltester.com](mailto:Zhongli@zltester.com)

Address: [No.62, Xinhe Management of Area, Wanjiang District, Dongguan city, Guangdong province ,China](#)



GB/T21196(national standard technical committees) GB/T4802.2 GB/T13775 FZ/T20020  
ISO12945-2 ISO12947 ASTM D4966 ASTM D4970 ASTM D3886 JIS  
L1096 DIN53863 DIN53865 BS3424 BS5690 BS EN388 BS EN530 IWS Tm196/ TM112 M & S

### Technical parameters

Model	ZL-5006 T Martin date Abrasimeter
Station number	9 station
Count display	a. Estimated counting:0~999999 times b. Total counting:0~999999 times
Maximum dynamic range	24±0.5mm ,60.5±0.5mm
Weight of pressure thing	a.Gripper:200±1g b. Cloth samples hammer:395±2g c. Furniture accessories sample hammer:594±2g d. Stainless steel butterfly piece:260±1g
Effective friction diameter of grinding block	A type: 200g (1.96N) friction head $\phi$ 28.8-0.084mm B type: 155g (1.52N) friction head $\phi$ 90-0.10mm
The relative velocity of Gripper and the grinding station	50-2r/min
Weight of pressure hammer	2385±10g
Dimensions	885mm×600mm×410mm(L×W×H)
Weight	150kg
Power	Ac220V,50Hz